

# CAMEL JET 1600

TRUCK MOUNTED SEWER CLEANER



Since 1973



## PERFORMS WELL UNDER PRESSURE

Camel Jet is the undisputed powerhouse for keeping sanitary and storm sewer lines, laterals, and drainage lines clean and free flowing. Its time proven high pressure water jetting system utilizes a continuous flow of 65 or 80 gpm (246.1 or 302.8L) and pressure up to 2,500 PSI (172.5 Bars) from positive displacement water pumps.


But, this is only one reason why Camel Jet 1600 belongs in your fleet. Another is choice. From water pumps to drive systems to piping and hose reel location, a unit can be customized to fit



your needs.

Having the option of selecting from various drive systems -- auxiliary gas or diesel engines, Hydrostatic, Hotshift PTO's, or splitshaft transfer case enhances Camel Jet flexibility.

**Rear-mount 180° Articulating Hose Reel  
with Patented Containment System**



**Convenient access to major components  
allows for quick and easy maintenance.**

Select from front or rear fixed or articulating hose reels and you have a customized unit with total operator convenience. And the Lexan Containment System helps protect the operator from hose rupture or high pressure water.

The Camel Jet carries 1,600 gallons (6,056.7L) of water in three modular tanks. Formed of rotationally molded polyethylene with ultra violet stabilizers, costly repairs associated with metal tanks are eliminated.

When you need a sewer cleaner with pressures and flows to perform to your specifications -- specify Camel Jet.



## Super Products

Worldwide Cleaning Technology  
Since 1973

# CAMEL JET 1600 TRUCK MOUNTED SEWER CLEANER

## Specifications & Options

### STANDARD WATER TANK SYSTEM

- Capacity - 1,600 US gallons (6,056.7L)
- Three tank modular self-baffle design
- Rotational molded polyethylene
- Anti-syphon air gap protection
- Curbside fill 2 1/2" (63.5mm)
- Inspection ports
- Water level sight tube
- Tank drain
- Mounting saddle

### HIGH PRESSURE WATER SYSTEM

- Heavy-duty Triplex continuous flow water pumps
- 50 GPM (189.3LPM) at 2000 PSI (138 bars) - optional
- 65 GPM (246.1LPM) at 1400 PSI (96.6 Bars) - optional
- 65 GPM (246.1LPM) at 2000 PSI (138 Bars) - **standard**
- 80 GPM (302.8LPM) at 2000 PSI (138 Bars) - optional
- Inline strainer
- Washdown gun/connection
- Relief valve/rebuildable

### POWER DRIVE SYSTEMS

- PTO-belt drive
- Splitshaft transfer case-belt drive
- Hydrostatic direct-drive
- Auxiliary engine-belt drive

### CONTROLS & GAUGES

- Water pump PTO - on/off
- Water pressure gauge
- Engine throttle - adjustable
- Reel speed control
- Water flow control valve

### HOSE REEL ASSEMBLY

- Rear or front fixed - **standard**
- Level wind - manual
- 800' (243.8m) capacity
- Single chain drive
- Containment shield
- Hydraulic pressure gauge

### **NOTE:**

**Sewer hose not included**

### STANDARD ACCESSORIES

- Operation, parts and service manuals (2)
- Full length tool trays
- Mud flaps - rear
- Painted white enamel color
- ICC lights and reflectors

### PARTIAL LIST OF OPTIONS

- Articulating hose reel --
  - Rear-mounted
  - Front-mounted
- Optional tank sizes --
  - 1,000 gallon (3,785.4L)
  - 2,000 gallon (7,570.8L)
  - 2,500 gallon (9,463.5L)
  - 3,000 gallon (11,356.2L)
- PSI up to 2,500 (172.5 Bars)
- Cold weather recirculation
- 1/2" (12.7mm) hose reel
- Footage counter
- Sewer hose
- Tigertail hose guide
- Dual fill system
- Tank strainer
- Dual chain drive
- Direct reel drive
- Urethane paint finish
- Tool box
- Side decorator panels
- Arrow board
- Beacon lights

---

See your Authorized Camel Dealer



## Super Products

Worldwide Cleaning Technology  
Since 1973

P.O. Box 270128 Milwaukee, WI 53227 USA

262-784-7100 800-837-9711 Fax 262-784-9561

Email: [sales@superproductscorp.com](mailto:sales@superproductscorp.com) • [www.superproductscorp.com](http://www.superproductscorp.com)

Illustrations shown may include optional equipment and accessories and may not include all standard equipment.

© 2000 Super Products Corporation Printed in U.S.A. Form 10005-811R